

DATASHEET

FA Control Network Communication Module MVI69-FLN

The MVI69-FLN FA Control Network communication module is a single-slot solution that allows Rockwell Automation CompactLogix processors to communicate with FL-net protocol-compatible devices. The module implements the FL-net version 2.00 (OPCN-2) specification, as defined by JEMA (The Japan Electrical Manufacturers Association) for the standard FA control network. FL-net is a master-less system.

The MVI69-FLN module acts as a gateway between the FL-net network and the CompactLogix/MicroLogix backplane. The data transfer from the CompactLogix/MicroLogix processor is asynchronous from the actions on the FL-net network. The module's internal database can be used to exchange Area 1 and Area 2 cyclic, network, and module status data between the processor and the FL-net network.

FL-net is a peer-to-peer networking system. All FL-net devices transfer data using two shared databases with fixed sizes. The MVI69-FLN module accepts commands to control and monitor the data stored in these two databases. This data is passed between the module and the CompactLogix/MicroLogix processor over the backplane for use in customer applications.



Features

Benefits

FL-net Network	<ul style="list-style-type: none"> ◆ Peer-to-Peer (masterless) token-passing network control method ◆ FA link protocol on Ethernet UDP/IP ◆ Cyclic data transfer supports virtual memory Area 1 and Area 2. The cyclic data is mapped to the module's I/O area.
ProSoft Configuration Builder software included	<ul style="list-style-type: none"> ◆ Graphical drag-and-drop configuration tool for simple module configuration ◆ Easy-to-use diagnostics window with menu-driven hardware and protocol diagnostics ◆ View module database contents through serial connection to a desktop PC
Backed by ProSoft Technology	<ul style="list-style-type: none"> ◆ 20-year history of delivering high-quality, reliable solutions designed with you in mind ◆ Free, unlimited, worldwide Technical Support by phone for pre-sale, set-up, or troubleshooting support helps you get going sooner and stay running longer ◆ Three-Year Warranty ensures reliability and protects against equipment failures ◆ Free ProSoft software tools tightly integrate with our hardware - A simple and quick, total solution to help you make our products fit your applications

Configuration

ProSoft Configuration Builder (PCB) provides a PC-based software configuration solution for management of module configuration files, as well as viewing communication and network diagnostics. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations into new projects.

General Specifications

- Single-slot, 1769 backplane-compatible
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module.
- Ladder Logic is used for data transfer between module memory and processor controller tags. A sample ladder file with AOI is included.
- Configuration data obtained from configuration text file downloaded to module. A sample configuration file is included.
- Supports CompactLogix and MicroLogix 1500 LRP Controllers except 1769-L23E-QBFC1B, 1769-L16x, and 1769-L18x.

Functional Specifications

- Personality Module: Incorporates a non-volatile Compact Flash memory for storing the module's setup and network configuration data (or personality). This allows restoring of a module by simply exchanging the Personality Module with no PC or configuration required.
- Web server: Provides product information and firmware updates.

Server Functionality

- Log data read service
- Log data clear service
- Network Parameter Read
- Return Message
- Profile Read
- Network Management Table: According to FL-net version 2.00 specification
- Own-node Management Table: According to FL-net version 2.00 specification
- Participating Node Management Table: According to FL-net version 2.00 specification
- Network configurable via a text file

Hardware Specifications

Specification	Description
Dimensions	Standard 1769 single-slot module
Current Load	800 mA max @ 5 VDC Power supply distance rating of 2 (L43 and L45 installations on first 2 slots of 1769 bus)
Operating Temp.	0°C to 60°C (32°F to 140°F)
Storage Temp.	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5% to 95% (with no condensation)
LED Indicators	Power and Module Status Application Status CFG Port Activity Ethernet Port Activity Error Status
CFG Port (CFG)	RJ45 (DB-9M with supplied cable) RS-232 only No hardware handshaking
App Port (Ethernet modules)	10/100 Base-T Ethernet compatible interface Electrical Isolation 1500 Vrms at 50 Hz to 60 Hz for 60 s, applied as specified in section 5.3.2 of IEC 60950: 1991 Ethernet Broadcast Storm Resiliency = less than or equal to 5000 [ARP] frames-per-second and less than or equal to 5 minutes duration
Shipped with Unit	RJ45 to DB-9M cables for each port 6-foot RS-232 configuration cable



Where Automation
Connects™

Global Distribution

We think like you do

ProSoft Technology® products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our web site at:

www.prosoft-technology.com

Global Support

We are there for you

All ProSoft Technology products are backed with free, unlimited technical support. Contact our worldwide Technical Support team directly by phone or email.

Global Offices

We are where you are

ProSoft Technology has regional offices worldwide available to help you with all your industrial application needs. If you need help choosing a ProSoft Technology solution for your particular application check out our contact information under distributor sales on the web site at:

www.prosoft-technology.com

Whether your application is large or small, our technical professionals are there to help you choose the right communication solution.

Agency Approvals and Certifications

Agency

ATEX

DNV

CE

CB Safety

GOST-R

CSA

cULus



Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. For a complete list of products, visit our web site at:

www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

FA Control Network Communication Module

MVI69-FLN

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:

www.prosoft-technology.com

and select *Where to Buy* from the menu.

Copyright © 2014 ProSoft Technology, Inc. All rights reserved. 10/2/2014

Specifications subject to change without notice.